

WATERPROOF SALT TESTER

... the next generation

Waterproof SaltTestr™

0 to 10.00 ppt

- Large Display
- $\pm 1\%$ Full Scale Accuracy
- Automatic Temperature Compensation
- Battery-Level Indicator
- Non-Volatile Memory
- Hold and Auto Power-Off Function



EUTECH
INSTRUMENTS
Technology Made Easy ...



**Waterproof
SaltTestr**



LARGE DISPLAY SCREEN

Displays mode, ATC, battery level.



WATERPROOF, ANTI-ROLL DESIGN

IP67 rated housing keeps tester waterproof even under wet conditions. Unique anti-roll ribbed design ensures firm grip. Light weight tester floats when accidentally drops into water.



USER-REPLACEABLE SENSOR

Replace the sensor yourself! No tools or soldering is necessary. Sensor element is of SS316 and ingeniously recessed for protection. The superior chemical durability of the VALOX® sensor casing gives you years of trouble free operation. Minimal maintenance is required.



PUSH-BUTTON CALIBRATION

Calibration buttons are neatly tucked away in the battery compartment to avoid unnecessary tampering.

HOLD FUNCTION

Hold measured values for later reading and recording. Especially useful when you are in dimly lit and confined areas.

WARRANTY

Eutech Instruments warrants its tester free from manufacturing defects for 2 years and electrode for 6 months.

APPLICATIONS

Aquaculture • Aquariums & fish farms
• Swimming pools, food production, etc.



SELF-DIAGNOSTIC MESSAGES:

▣ : Battery power level indicator
Or : Over range, for Salinity values
Er.1 : Calibration error

AUTO-POWER OFF

Tester automatically powers off after 8.5 minutes of non-use to conserve battery life and save you money.

METER SPECIFICATIONS

Range	0 - 10.00 ppt
Resolution	0.10 ppt
Accuracy	±1% of Full Scale
Calibration	1 point
Operating Temperature	0 to 50 °C
Automatic Temperature Compensation	0 to 50 °C ATC coefficient, $\beta = 2\% / ^\circ\text{C}$
Battery Life	4 x 1.5V (Type: A76, LR44, V136A); > 150 hours
Dimensions; Weight	Tester: 16.5cm x 3.8cm; 90g Boxed: 22cm x 6cm x 5cm; 170g

1 ppt = 1000 ppm

ORDERING INFORMATION

Order No.	Item
SALTEST10	Waterproof Salinity Tester
EC-TDSWPSENNEW	Replacement SaltTestr Sensor
EC-POUCH-01	Carrying Pouch
60X017004	Alkaline Batteries (2 pcs)
33X367001	Lanyard, Eutech
EC-NACL-5PPT	Calibrating Solution, 5 ppt (g/L)

Eutech also provides tester accessories and calibration standards. Refer to separate brochures for information.

® VALOX is a registered trademark of GE Plastic.

We reserve the right to make changes, improvements and modifications to products shown.

EUTECH
INSTRUMENTS
Technology Made Easy ...

ISO 9001
CERTIFIED

Distributed By:

www.eutechinst.com
marketing@eutechinst.com

Singapore ♦ USA ♦ Netherlands ♦ Malaysia ♦ China